

**Overview**

Iso-Fuge MICRO15 is a high speed micro centrifuge with rotor capacity 12\*1.5/2ml. Speed and time can easily be set and displayed. The operation can be timed, continuous or short quick spin. It features imbalance detection with auto cut off and a Brushless DC motor, which is maintenance free, delivers better power / weight ratio and is suitable for extended runs.

**Features**

- Microprocessor controller with LED display
- Brushless motor- Maintenance free, delivers better power / weight ratio and fit for extended runs
- Imbalance detection with auto cut off
- Digital display for easy reading of parameters
- Lid lock safety - Lid opens automatically on run completion
- One touch short spin operation & RPM / RCF conversion
- Maximum speed of 15000 RPM
- Automatic lid release after run
- Supplied with 12 x 1.5ml / 2ml micro tube rotor



**Specifications**

Maximum RPM / RCF	15000 / 15596g
Rotor Capacity	12 x 1.5ml / 2.0ml micro tubes
Timer Setting	1 to 99 minutes & infinite mode
Display	Digital display
Electronic Safety Brake	Yes
Noise Level	< 60 dB
Motor Type	Brushless DC motor
Dimensions (WxDxH) in mm	260 x 244 x 205 mm
Optional Rotor	Mini hematocrit rotor - 24 x 45 length capillary tubes

**Ordering Information**

CEN-MICRO15	Iso-Fuge Micro 15 High Speed Centrifuge, with rotor 12*1.5/2ml and reduction adaptors for 0.2 ml & 0.4/0.5 ml tubes, UK plug, 110-240V, 50/60Hz
CEN-MICRO15-HCT	Mini HCT rotor for 24 x 45 mm length capillary tubes



Quality Lab Systems  
Wimborne | Dorset  
BH21 7DG | England

E-mail: [info@QLSystems.co.uk](mailto:info@QLSystems.co.uk)  
Website: [www.QLSystems.co.uk](http://www.QLSystems.co.uk)