

Overview

The ThermaCell range of heating incubators consists of three models with different chamber capacities of 35L, 50L and 80L. The incubators are high quality, reliable and safe, with the air forcing convection with the blower fan installed at the back of the inner chamber. The internal surface has a semi circular arc at the corners for easy cleaning. Fiberglass is used for insulation to ensure accurate heating and preservation of temperature. The space between the shelves is adjustable.

Features

- Microprocessor controller with digital display
- Exterior made of stainless steel 304, inner chamber is galvanized sheet
- Inner glass door for easy observation
- Temperature range from RT+5 - 60°C



Specifications

Model	ThermaCell-35	ThermaCell-50	ThermaCell-80
Power Supply	220V, 50HZ		
Temperature Range	RT+5 - 65°C		
Display Resolution	0.1°C		
Temperature Variation	±1°C		
Ambient Temperature	+5 - 35°C		
Power Consumption	200W	250W	350W
Chamber Volume	35L	50L	80L
Interior Dimensions (W x D x H)	340 x 320 x 320mm	415 x 360 x 355mm	500 x 400 x 400mm
Overall Dimensions (W x D x H)	620 x 490 x 490mm	690 x 500 x 500mm	780 x 530 x 560mm
Shelves	2(pcs)		
Timing Range	1-9999 min		

Quality Lab Systems

Wimborne | Dorset

BH21 7DG | England

E-mail: info@QLSystems.co.uk

Website: www.QLSystems.co.uk



ThermaCell Heating Incubators

ThermaCell-35, ThermaCell-50, ThermaCell-80

Ordering Information

TINC-35	ThermaCell-35, heating incubator, 35 litres
TINC-50	ThermaCell-50, heating incubator, 50 litres
TINC-80	ThermaCell-80, heating incubator, 80 litres

Quality Lab Systems
Wimborne | Dorset
BH21 7DG | England

E-mail: info@QLSystems.co.uk
Website: www.QLSystems.co.uk



QUALITY LAB SYSTEMS